



**PETRO
MASTER**
TYRE

www.baygold.cn

Since 2010



P106

Suitable for long-
distance and highways


SIZE	PR	LL/SS	TREAD WIDTH	TREAD DEPTH
11R22.5	20	168/A8	230	15.5
295/80R22.5	18	152/149M	232	14.5



P118

Suitable for long-
distance and highways

SIZE	PR	LL/SS	TREAD WIDTH	TREAD DEPTH
11R22.5	18	149/146M	230	15.5
295/75R22.5	18	148/145L	226	14.5
295/80R22.5	22	160/157K	252	17.0
315/80R22.5	18	152/149M	242	18.0
205/85R16	14	118/114L	165	13.0
215/75R17.5	18	135/133J	187	14.0
235/75R17.5	18	143/141J	202	15.0
245/70R19.5	18	141/140K	212	16.0
7.50R16LT	16	125/121L	176	13.5



P197

Suitable for long-
distance and highways

SIZE	PR	LL/SS	TREAD WIDTH	TREAD DEPTH
11R22.5	18	149/146L	214	15.0
12R22.5	18	152/149L	226	14.0



P102

Specially designed for
heavy-duty, highways

SIZE	PR	LL/SS	TREAD WIDTH	TREAD DEPTH
12R22.5	18	152/149L	238	17.2



P268

Suitable for all kinds
of regional highways

SIZE	PR	LL/SS	TREAD WIDTH	TREAD DEPTH
6.50R16LT	12	110/105L	145	11.0
7.00R16LT	14	118/114L	160	11.5
7.50R16LT	16	125/121L	170	13.0
8.25R16LT	18	132/128L	187	14.0
11.00R20	18	152/149K	226	16.5
12.00R20	20	156/153K	240	17.0
11R22.5	18	149/146M	214	15.0
12R22.5	18	152/149K	246	18.0
315/80R22.5	20	157/154M	226	14.5



P217

Suitable for all kinds
of regional highways

SIZE	PR	LL/SS	TREAD WIDTH	TREAD DEPTH
12R22.5	18	152/149K	226	14.0



P196

Super steering for all
position

SIZE	PR	LL/SS	TREAD WIDTH	TREAD DEPTH
12R22.5	18	152/149L	246	18.0
11.00R20	20	153/150L	246	18.0



P299

Overload for regional
highways

SIZE	PR	LL/SS	TREAD WIDTH	TREAD DEPTH
11.00R20	20	152/149K	242	18.0
12.00R20	22	158/155K	242	18.0
315/80R22.5	20	156/153K	250	18.0



P205

Suitable for all kinds
of regional highways

SIZE	PR	LL/SS	TREAD WIDTH	TREAD DEPTH
7.00R16LT	14	118/114L	157	13.0
7.50R16LT	16	125/121L	176	14.5
8.25R16LT	18	132/128L	183	15.5
11.00R20	20	152/149K	226	16.5
12.00R20	20	156/153K	240	17.5
11R22.5	18	149/146K	220	16.0
315/80R22.5	20	157/154M	232	15.0



P517

Overloading long-distance drive tyre

SIZE	PR	LL/SS	TREAD WIDTH	TREAD DEPTH
295/80R22.5	18	152/149K	235	18.5
315/80R22.5	22	167D	260	23.0



DC980

Overloading long-distance drive tyre

SIZE	PR	LL/SS	TREAD WIDTH	TREAD DEPTH
11R22.5	18	149/146M	230	21.0



PW02

Special formula for winter snow

SIZE	PR	LL/SS	TREAD WIDTH	TREAD DEPTH
11R22.5	18	149/146L	230	21.0
11R24.5	18	152/149L	230	21.0



P569

Designed for mining

SIZE	PR	LL/SS	TREAD WIDTH	TREAD DEPTH
11R24.5	18	152/149F	230	22.0
12R22.5	18	152/149J	245	22.0
295/80R22.5	18	152/149M	245	19.5



P802

Overloading long-distance drive tyre

SIZE	PR	LL/SS	TREAD WIDTH	TREAD DEPTH
12R22.5	18	152/149K	240	18.0
9.00R20	18	144/142K	220	17.5
10.00R20	18	149/146K	230	18.5
11.00R20	20	152/149K	230	19.0
12.00R20	22	156/153K	240	19.5



P588

Overloading long-distance drive tyre

SIZE	PR	LL/SS	TREAD WIDTH	TREAD DEPTH
215/75R17.5	18	135/133J	187	17.5
12R22.5	18	152/149K	252	24.5
295/80R22.5	18	152/149M	256	22.5
315/70R22.5	20	156/150K	270	21.0
315/80R22.5	22	160/157K	265	22.5



P568

Designed for mining

SIZE	PR	LL/SS	TREAD WIDTH	TREAD DEPTH
225/80R17.5	18	129/127K	192	17.5
235/75R17.5	18	143/141J	202	17.5
7.50R16LT	16	125/121K	170	16.5
8.25R16LT	18	132/128K	187	16.5



P810

Designed for overload mining

SIZE	PR	LL/SS	TREAD WIDTH	TREAD DEPTH
11.00R20	20	152/149K	250	21.5
12.00R20	22	158/155K	250	21.5



P831

Designed for overload mining

SIZE	PR	LL/SS	TREAD WIDTH	TREAD DEPTH
12R22.5	20	152/149F	242	24.0
11.00R20	20	153/150F	240	24.5
12.00R20	22	158/155F	250	25.0



P822

Designed for overload mining

SIZE	PR	LL/SS	TREAD WIDTH	TREAD DEPTH
11.00R20	18	152/149F	225	24.0
12.00R20	22	156/153F	245	25.0



P832

Designed for overload mining

SIZE	PR	LL/SS	TREAD WIDTH	TREAD DEPTH
11.00R20	20	152/149F	250	25.5
12.00R20	24	158/155D	260	27.0



www.baygold.cn

Add:No.157 Jinggangshan Road,E.T.D.Z.Huangdao,Shandong,China